



PVC Pressure Pipe Fittings

PVC Pressure Pipe Fittings

Design

The Waterworks PVC Pressure Pipe fittings are well known for their excellent chemical and corrosion resistance and are an extremely durable and cost-effective option. The majority of the fittings are white, matching series 1 PVC pressure pipes, however, some of the larger fittings are dark grey due to their manufacturing origin. All threaded fittings in the Series 1 PVC fitting range have BSP threads, and all fittings have a tapered socket design to create an interference fit. So when you insert the pipe into the fitting it will tighten up before the pipe reaches the end of the socket. These PVC fittings are not regarded as being UV resistant and may be subject to some deterioration over time when exposed to UV radiation.

Sizes

15mm - 300mm

*Sizes available may differ for some fittings.

Applications

- Water reticulation
- Irrigation
- Waste disposal
- · Swimming pools
- Water treatment
- · Chemical handling systems

Pressure Rating

Up to PN18

*The pressure rating must be de-rated if the fittings are to be used at elevated temperatures above 20°C.

Temperature Range

4°C to 40°C Max 60°C

Seals

The following fittings have EPDM seals:

- 1. PVC socket unions
- 2. Compression couplings
- 3. Slip Fix Repair Couplings
- 4. Gibault Couplings







Scan the QR code to view our PVC Pressure Pipe Fittings online.









Contact us to discuss your pipeline project 0800 387 677



Auckland | New Plymouth | Wellington

Head Office: 90 Hurlstone Drive, New Plymouth **e:** support@waterworksnz.co.nz **www.waterworksnz.co.nz**